



4/8/2009

RELIABILITY MONITOR REPORT  
FOR

**PLCC Package**

**MAXIM Integrated Products**

120 San Gabriel Dr.  
Sunnyvale, CA 94086

This Report was prepared by  
Maxim Reliability Engineering

**Summary:**

The data in the tables that follow was generated as the result of an on-going Package Reliability Monitor. The specific assemblies included in this package monitor are:

ASSY SITE	PINS PACKAGE
ATP (Amkor, PI)	52 PLCC (Pb-Free)

The calculated failure rate for this assembly is:

**FAILURE RATE: MTTF (YRS): 9048 FITS: 12.6**

The parameters used to calculate this failure rate are as follows:

**Cf: 60% Ea: 0.7 Tu: 25 °C**

The reliability data follows. At the start of this data is a description of the assembly vehicle used to generate this reliability data. The next section is the detailed reliability data for each stress. The reliability data section includes the latest data available. This report covers data between 7/1/2007 and 6/30/2008.

---

**Assembly Information:**

Package Type: PLCC (Pb-Free)

Date Code Range: 0726 to 0726

---

**OPERATING LIFE**

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	FA NO
HIGH TEMP OP LIFE	0726	DS87C530	125C, 5.5 VOLTS	1000 HRS	77	0	
				<b>Total:</b>		<b>0</b>	

---

**STORAGE LIFE**

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	FA NO
STORAGE LIFE	0726	DS87C530	150C	1000 HRS	77	0	
				<b>Total:</b>		<b>0</b>	

**FAILURE RATE: MTTF (YRS): 9048 FITS: 12.6**